KÖSTER Pipe Flashing light grey

Technical Data Sheet RT 905

Issued: 2025-10-20



Features
Intended use:
For edging round penetrations such as cable ties, lightning protection, and cable bushings.

Material:
FPO-PE-based elements for connection to the appropriate material variant, such as KÖSTER TPO roofing and waterproofing membranes. The materials are weather-resistant, UV-stable, cold-impact-resistant, and root-resistant.

Processing:
The KÖSTER Pipe Flashing is applied to the installed roof waterproofing using hot air in accordance with the KÖSTER installation instructions. The use of TPO cleaner is recommended.
The upper edge must be made rainproof, e.g., with the PE shrink tubing supplied.
The specifications of the flat roof guideline and DIN 18531 must be observed.

Technical Data
Color: light gray
Height [mm]: 300
Inner diameter [mm]: 10 / 20 / 30 / 42 / 50
Material thickness [mm]: 3

Packaging
RT 905 piece

Storage
DN10 item number: RT 905 001
DN20 item number: RT 905 002
DN30 item number: RT 905 005
DN42 item number: RT 905 003
DN50 item number: RT 905 006

R - Roofing membranes, roof waterproofing

The information contained in this technical data sheet is based on the results of our research and on our practical experience in the field. All given test data are average values which have been obtained under defined conditions. The proper and thereby effective and successful application of our products is not subject to our control. The installer is responsible for the correct application under consideration of the specific conditions of the construction site and for the final results of the construction process. This may require adjustments to the recommendations given here for standard cases. Specifications made by our employees or representatives which exceed the specifications contained in this technical guideline require written confirmation. The valid standards for testing and installation, technical guidelines, and acknowledged rules of technology have to be adhered to at all times. The warranty can and is therefore only applied to the quality of our products within the scope of our terms and conditions, not however, for their effective and successful application. This guideline has been technically revised; all previous versions are invalid.

KÖSTER BAUCHEMIE AG • Dieselstraße 1-10 • D-26607 Aurich • Tel. 04941/9709-0 • info@koester.eu • www.koester.eu